

HAND TAPS

JIS Hand Taps with Straight flute for Metric fine Thread























for cutting through hole / blind hole







T202 Tap	s Serie	es									
产品编号(code)	公 制	牙 (MF)	Size U							Unit:mm	Net Price
T202	Size	Pitch	L	l	l1	d	k	lĸ	Туре	Flutes	T202
00200250	M2	0.25	42	7	15	3.0	2.5	5	2	3	
00230250	M2.3	0.25	42	7	15	3.0	2.5	5	2	3	-10-12-12-12-12-12-12-12-12-12-12-12-12-12-
00250350	M2.5	0.35	44	8	16	3.0	2.5	5	2	3	Harrison Januari
00260350	M2.6	0.35	44	8	16	3.0	2.5	5	2	3	
00300600	МЗ	0.60	46	11	18	4.0	3.2	6	2	3	
00300350	МЗ	0.35	46	9.5	18	4.0	3.2	6	2	3	
00350350	M3.5	0.35	48	9.5	20	4.0	3.2	6	2	3	400 C (200 C) - 400 C (400 C)
00400750	M4	0.75	52	13	20	5.0	4.0	7	2	3	
00400500	M4	0.50	52	13	20	5.0	4.0	7	2	3	namen manua
00450500	M4.5	0.50	55	13	21	5.0	4.0	7	2	3	
00500500	M5	0.50	55	13	25	5.5	4.5	7	2	3	
00500750	M5	0.75	60	16	25	5.5	4.5	7	2	3	
00600750	M6	0.75	62	19	28	6.0	4.5	7	2	3	
00600500	M6	0.50	55	13	25	6.0	4.5	7	2	3	
00700750	M7	0.75	65	19	30	6.2	5.0	8	3	4	
00700500	M7	0.50	55	13	25	6.2	5.0	8	3	4	
00801000	M8	1.00	70	22		6.2	5.0	8	3	4	
00800750	M8	0.75	70	22		6.2	5.0	8	3	4	
00901000	M9	1.00	72	22		7.0	5.5	8	3	4	10.7 1100
01001250	M10	1.25	75	24		7.0	5.5	8	3	4	
01001000	M10	1.00	75	24		7.0	5.5	8	3	4	
01000750	M10	0.75	75	22		7.0	5.5	8	3	4	
01000500	M10	0.50	55	13		7.0	5.5	8	3	4	
01101250	M11	1.25	80	25		8.0	6.0	9	3	4	



TZ02

HAND TAPS

JIS Hand Taps with Straight flute for Metric fine Thread

产品编号(code)	公 制 牙 (MF)		Size Unit:mr							Unit:mm	Net Price
T202	Size	Pitch	L	l	l ₁	d	k	lĸ	Туре	Flutes	T202
01101000	M11	1.00	80	25		8.0	6.0	9	3	4	
01100750	M11	0.75	75	22		8.0	6.0	9	3	4	
01201500	M12	1.50	82	29		8.5	6.5	9	3	4	
01201250	M12	1.25	82	29		8.5	6.5	9	3	4	
01301750	M13	1.75	85	29		9.5	7.0	10	3	4	Fo. 100 100
01301500	M13	1.50	85	29		9.5	7.0	10	3	4	
01401500	M14	1.50	88	30		10.5	8.0	11	3	4	
01401250	M14	1.25	88	30		10.5	8.0	11	3	4	
01401000	M14	1.00	88	30		10.5	8.0	11	3	4	DESIGN ROVER
01501500	M15	1.50	90	30		10.5	8.0	11	3	4	
01501000	M15	1.00	90	30		10.5	8.0	11	3	4	
01601500	M16	1.50	95	32		12.5	10	13	3	4	
01601000	M16	1.00	95	32		12.5	10	13	3	4	200020000000000000000000000000000000000
01701500	M17	1.50	95	32		13.0	10	13	3	4	D. C. OCT.
01701000	M17	1.00	95	32		13.0	10	13	3	4	
01802000	M18	2.00	100	37		14.0	11	14	3	4	Towns of Towns
01801500	M18	1.50	100	37		14.0	11	14	3	4	
01801000	M18	1.00	95	30		14.0	11	14	3	4	
01901500	M19	1.50	105	37		14.0	11	14	3	4	
01901000	M19	1.00	95	30		14.0	11	14	3	4	
02002000	M20	2.00	105	37		15.0	12	15	3	4	
02001500	M20	1.50	105	37		15.0	12	15	3	4	
02202000	M22	2.00	115	38		17.0	13	16	3	4	130 000
02201500	M22	1.50	115	38		17.0	13	16	3	4	
02201000	M22	1.00	95	30		17.0	13	16	3	4	
02301500	M23	1.50	115	38		18.0	14	17	3	4	1000 300 400 4000
02402000	M24	2.00	120	45		19.0	15	18	3	4	
02401500	M24	1.50	120	45		19.0	15	18	3	4	100 mg 1000

▶ 第一攻 – 9牙 /Taper Tap...9 Pitches

▶ 第二攻 - 5牙/Plug Tap...5 pitches

▶ 第三攻 – 1.5牙/Bottoming Tap..1.5Pitches

第三攻(上) 第三攻(中) 第一攻(先) Taper Tap

- ► Specially slow spiral design (特殊低螺旋角设计)
- ► Tialn coating for good performance and long life (铝钛处理以保证寿命之能力)
- ► JIS standard (日标)
- ► Made of HSS-Co steel(钴高速钢制造)
- ▶ Ideal for use on Casting Iron(专用硬化加工)